

Technical Informations

Rim material

RAL

RIMS

Product group	Rims
Item number	30855025
Valid rim size	8.50 JA x 12 H2
Rim connection	6/161/205
Rim colour	Red
Brand	Vlukon

steel

RAL3000





Load capacity of rim 1 [kg]	1150
Speed Rims 1 [km/h]	5
Load capacity of rim 2 [kg]	950
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	8,00
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Number of drain holes	3
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Cone
Countersinking of the cone [°].	C90
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No