

Technical Informations

RIMS

Product group	Rims
Item number	30855027
Valid rim size	8.50 JA x 12 H2
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Red
Brand	Vlukon





Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	975
Speed Rims 2 [km/h]	40

Maximum speed [km/h]. 40 Type of drive Towed axle Nettogewicht [kg] (gültig) 7,80 Hump H2 VS H Valve protection Single / multi-part einteilig Rim material steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL3000
Cavity Sealed	No
Disc thickness [mm]	4
Knurling	without knurling
Verschweißung beidseitig	No
Number of drain holes	3
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No