Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	30856021
Valid rim size	6 J x 15 H2
Rim connection	5/57/112
Offset (mm)	+47
Rim colour	Silver
Brand	Accuride





Technical Informations

Load capacity of rim 1 [kg]	650
Speed Rims 1 [km/h]	200
Maximum speed [km/h].	200
Nettogewicht [kg] (gültig)	7,80
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Car model	Caddy Life

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.