

## **RIMS**

Product group	Rims
Item number	30856085
Valid rim size	6.5 J x 16 H2
Rim connection	6/84/130
Offset (mm)	+62
Rim colour	Silver
Brand	Accuride





## **Technical Informations**

Load capacity of rim 1 [kg]	1215
Speed Rims 1 [km/h]	170
Maximum speed [km/h].	170
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	11,28
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	5.10

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Car model	Sprinter
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
hub hole diameter [mm].	84
Bolt hole circle diameter [mm]	130
Valve seat	External Valve
Valve hole diameter [mm]	11.5
Preassembled valve	No