Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	30895259
Valid rim size	7.00 A x 8 H2
Rim connection	5/79.5/114.3
Rim colour	White
Brand	Vlukon



Technical Informations

Load capacity of rim 1 [kg]	525
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	3,50
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9003
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	12.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	79.5
Bolt hole circle diameter [mm]	114.3
Valve seat	External Valve
Valve hole diameter [mm]	12.5
Preassembled valve	No