

Verschweißung beidseitig

No

RIMS

Product group	Rims
Item number	30962080
Valid rim size	14.00 X 19.5
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Brand	BOKA Wheel



Technical Informations		
Load capacity of rim 1 [kg]	4500	
Speed Rims 1 [km/h]	100	
Maximum speed [km/h].	100	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	39,81	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	внс
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	Yes
Valve design	Metal valve
Valve designation ETRTO	V3.12.1
Valve length [mm]	40
Valve angle [°]	90
Valve cap Material	Steel