

## RIMS

Product group	Rims
Item number	30963006
Valid rim size	6.00 x 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+122.5
Half centre distance (HMA) [mm]	135.5
Rim colour	Silver
Brand	BOKA Wheel



**BOKA** WHEEL

## Technical Informations

Load capacity of rim 1 [kg]	2725
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	27,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

---

Ventilation holes	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90
Valve angle [°]	27
Valve cap Material	Steel