

RIMS

Product group	Rims
Item number	30963009
Valid rim size	6.75 X 17.5
Rim connection	10/176/225
Bolt hole design	M20/M22
Offset (mm)	+125
Half centre distance (HMA) [mm]	138
Rim colour	Black
Brand	BOKA Wheel



Technical Informations	
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2750
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	27,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Metal valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90
Valve angle [°]	27
Valve cap Material	Steel