

RIMS

Product group	Rims
Item number	30963011
Valid rim size	6.75 X 17.5
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Black
Brand	BOKA Wheel



Technical Informations		
Load capacity of rim 1 [kg]	3135	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	2725	
Speed Rims 2 [km/h]	100	
Maximum speed [km/h].	100	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	26,50	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9005	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	ВНС
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No