

RIMS

Product group	Rims
Item number	30963013
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+130
Half centre distance (HMA) [mm]	143
Rim colour	Silver
Brand	BOKA Wheel



BOKA WHEEL

Technical Informations

Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2757
Speed Rims 2 [km/h]	140
Load capacity of rim 3 [kg]	2500
Speed Rims 3 [km/h]	140
Maximum speed [km/h].	140
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	27,50
Hump	kein Hump
Single / multi-part	einteilig

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Metal valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90.0
Valve angle [°]	27
Valve cap Material	Steel