Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	30963033
Valid rim size	11.75 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Black
Brand	BOKA Wheel





Technical Informations

Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	43,50
Hump	н
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No