

RIMS

Product group	Rims
Item number	30963060
Valid rim size	7.50 x 19.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+138.5
Half centre distance (HMA) [mm]	151
Rim colour	Silver
Brand	BOKA Wheel



Technical Informations		
Load capacity of rim 1 [kg]	2900	
Speed Rims 1 [km/h]	90	
Maximum speed [km/h].	90	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	34,20	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	
Verschweißung beidseitig	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	внс
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No