

RIMS

Product group	Rims
Item number	30964055
Valid rim size	9.00 x 22.5
Rim connection	10/281/335
Bolt hole design	M20/M22
Offset (mm)	+153
Half centre distance (HMA) [mm]	175
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	4125
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	3710
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	24,60
Hump	kein Hump
Single / multi-part	einteilig
Rim material	aluminium
Surface treatment	Polish+Accu-Shield
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve designation ETRTO	V3.20.7
Valve length [mm]	70.0
Valve angle [°]	27