

RIMS

| | |
|---------------------------------|--------------|
| Product group | Rims |
| Item number | 30964115 |
| Valid rim size | 11.75 x 22.5 |
| Rim connection | 10/281/335 |
| Bolt hole design | M20/M22 |
| Offset (mm) | +135 |
| Half centre distance (HMA) [mm] | 163 |
| Rim colour | Silver |
| Brand | Accuride |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 5000 |
| Speed Rims 1 [km/h] | 130 |
| Maximum speed [km/h]. | 130 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 25,90 |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | aluminium |
| Surface treatment | Polish+Accu-Shield |
| Cavity Sealed | No |
| Disc thickness [mm] | 28 |

| | |
|--------------------------------|----------------|
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | HB |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | M22 |
| Bolt hole diameter [mm] | 26 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | Yes |
| Valve design | Metal valve |
| Valve designation | 54MS00 |