

## **RIMS**

Product group	Rims
Item number	31267882
Valid rim size	11.75 x 19.5
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	4250	
Speed Rims 1 [km/h]	100	
Maximum speed [km/h].	100	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	44,00	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	
Disc thickness [mm]	13	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No