

RIMS

Product group	Rims
Item number	31267918
Valid rim size	14.00 x 19.5
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	5750	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	5150	
Speed Rims 2 [km/h]	65	
Maximum speed [km/h].	65	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	43,10	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No