

## RIMS

Product group	Rims
Item number	31459993
Valid rim size	6.00 X 17.5
Rim connection	10/176/225
Bolt hole design	A33
Offset (mm)	+122.5
Half centre distance (HMA) [mm]	133
Rim colour	Silver
Brand	Accuride



## Technical Informations

Load capacity of rim 1 [kg]	3150
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	3000
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	22,80
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 ES 36
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Angled valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90.0
Valve angle [°]	27