

RIMS

Product group	Rims
Item number	31459998
Valid rim size	6.00 x 17.5 H
Rim connection	6/161/205
Bolt hole design	M18
Offset (mm)	+114
Half centre distance (HMA) [mm]	125
Rim colour	Silver
Brand	Accuride





Technical Informations	
Load capacity of rim 1 [kg]	1850
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	1750
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	20,50
Hump	н
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	6
Bolt hole design EUWA	M18
Bolt hole diameter [mm]	21
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No