Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	31460000
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	A33
Offset (mm)	+129.5
Half centre distance (HMA) [mm]	140
Rim colour	Silver
Brand	Accuride



Allgemeine Produktabbildung. Artikel kann abweichen



Technical Informations

Load capacity of rim 1 [kg]	3150
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	3000
Maximum speed [km/h].	130
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	25,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 ES 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Preassembled valve	No