

RIMS

Product group	Rims
Item number	31460011
Valid rim size	6.75 X 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+129.5
Half centre distance (HMA) [mm]	140
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	3150
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	3000
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	24,80
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Angled valve
Valve designation ETRTO	V3.20.4
Valve length [mm]	90.0
Valve angle [°]	27