

RIMS

Product group	Rims
Item number	31460026
Valid rim size	7.50 x 22.5
Rim connection	8/221/275
Bolt hole design	M20
Offset (mm)	+147.5
Half centre distance (HMA) [mm]	160
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	2900
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	35,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	HB
Number of bolt holes	8
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Angled valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45