

RIMS

Product group	Rims
Item number	31460033
Valid rim size	8.25 x 22.5
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+152.5
Half centre distance (HMA) [mm]	165
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	3550
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	3150
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	35,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45