

## RIMS

Product group	Rims
Item number	31460040
Valid rim size	7.50 x 19.5 H
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+138.1
Half centre distance (HMA) [mm]	150
Rim colour	Silver
Brand	Accuride



## Technical Informations

Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	2650
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,80
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	HB
Number of bolt holes	8
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Angled valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45