

## RIMS

Product group	Rims
Item number	31460043
Valid rim size	7.50 x 19.5
Rim connection	10/176/225
Bolt hole design	A33
Offset (mm)	+138
Half centre distance (HMA) [mm]	151
Rim colour	Silver
Brand	Accuride



## Technical Informations

Load capacity of rim 1 [kg]	2725
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	28,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 ES 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Angled valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45