

RIMS

Product group	Rims
Item number	31460045
Valid rim size	6.75 x 19.5
Rim connection	8/221/275
Bolt hole design	B33
Offset (mm)	+133.1
Half centre distance (HMA) [mm]	145
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	2500
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	2360
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	23,80
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	8
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Angled valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45