Bohnenkamp Moving Professionals

21.09.2024

RIMS

Product group	Rims
Item number	31460246
Valid rim size	15.00 x 22.5 H
Rim connection	10/281/335
Bolt hole design	M22
Rim colour	Silver
Brand	Accuride





Technical Informations

Load capacity of rim 1 [kg]	5300
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Nettogewicht [kg] (gültig)	49,60
Hump	н
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rim centering	НВ
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	36.0