

RIMS

Product group	Rims
Item number	31610045
Valid rim size	5.00 F - 10
Rim connection	5/110/160
Bolt hole design	A1
Rim colour	Red
Brand	Accuride



Technical Informations	
Load capacity of rim 1 [kg]	2350
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Nettogewicht [kg] (gültig)	12,05
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	five-part
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Rim design industry	Standard

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	160
Valve seat	External Valve
Preassembled valve	No