Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	31610064
Valid rim size	10.50 l x 12 H2
Rim connection	4/85/130
Offset (mm)	-52.5
Rim colour	Silver
Brand	Gianetti FAD

Technical Informations

Load capacity of rim 1 [kg]	1120
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	10,10
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Number of drain holes	4
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	4
Bolt hole diameter [mm]	14.5
hub hole diameter [mm].	85
Bolt hole circle diameter [mm]	130
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No