

## **RIMS**

Product group	Rims
Item number	31610095
Valid rim size	6 J x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Brand	Accuride





## **Technical Informations**

Load capacity of rim 1 [kg]	1285
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	12,00
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No