

RIMS

| | |
|------------------|-----------|
| Product group | Rims |
| Item number | 31610190 |
| Valid rim size | 8 J x 16 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Offset (mm) | -5 |
| Rim colour | Silver |
| Brand | Accuride |



Technical Informations

| | |
|-----------------------------|-----------|
| Load capacity of rim 1 [kg] | 2700 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 1800 |
| Speed Rims 2 [km/h] | 60 |
| Maximum speed [km/h]. | 60 |
| Nettogewicht [kg] (gültig) | 16,00 |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |

| | |
|--------------------------------|----------------|
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |