

RIMS

Product group	Rims
Item number	31612625
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+40
Rim colour	Silver
Brand	Gianetti FAD
Rim series	Profiline



Technical Informations

Load capacity of rim 1 [kg]	3500
Speed Rims 1 [km/h]	5
Load capacity of rim 2 [kg]	2000
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	1000
Speed Rims 3 [km/h]	20
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	50,00
Hump	H2
Valve protection	VSH

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No