

## RIMS

Product group	Rims
Item number	31612673
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Brand	Gianetti FAD
Rim series	Profiline+



## Technical Informations

Load capacity of rim 1 [kg]	7010
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5150
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	48,70
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel

---

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	10
<b>Bolt hole design EUWA</b>	B22 ES 36
<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No