

## RIMS

Product group	Rims
Item number	31612735
Valid rim size	DW 16 L x 24
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-10
Rim colour	Black
Brand	Gianetti FAD



## Technical Informations

Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	5000
Speed Rims 3 [km/h]	10
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	51,30
Hump	kein Hump
Valve protection	VSH

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Disc thickness [mm]	10
Knurling	with knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No