

RIMS

| Product group | Rims |
|----------------|--------------|
| Item number | 31655242 |
| Valid rim size | 6 J x 14 H2 |
| Rim connection | 6/110/150 |
| Rim colour | Silver |
| Brand | Gianetti FAD |



Allgemeine Produktabbildung. Artikel kann abweichen

Technical Informations

| Load capacity of rim 1 [kg] | 750 |
|-----------------------------|-------------------------------|
| Speed Rims 1 [km/h] | 16 |
| Maximum speed [km/h]. | 16 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 9,50 |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Ventilation holes | No |
|--------------------------------|----------------|
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 13 |
| hub hole diameter [mm]. | 110 |
| Bolt hole circle diameter [mm] | 150 |
| Valve seat | External Valve |
| Preassembled valve | No |