

## **RIMS**

Product group	Rims
Item number	31655250
Valid rim size	8.00 x 14.5
Rim connection	5/110/160
Bolt hole design	A1
Rim colour	Silver
Brand	Gianetti FAD

## **Technical Informations**

Load capacity of rim 1 [kg]	1700
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	12,20
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	160
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No