

RIMS

| | |
|------------------|---------------|
| Product group | Rims |
| Item number | 32010104 |
| Valid rim size | 13 LB x 15 H2 |
| Rim connection | 5/66.6/112 |
| Bolt hole design | A1 |
| Offset (mm) | -37 |
| Rim colour | Silver |
| Brand | Gianetti FAD |



Allgemeine Produktabbildung. Artikel kann abweichen

Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 1250 |
| Speed Rims 1 [km/h] | 25 |
| Load capacity of rim 2 [kg] | 900 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 17,50 |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |

| | |
|--------------------------------|----------------|
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole design EUWA | B14 ES 28 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 66.6 |
| Bolt hole circle diameter [mm] | 112 |
| Valve seat | External Valve |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |