

## **RIMS**

Product group	Rims
Item number	32010117
Valid rim size	13 LB X 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-10
Rim colour	Silver
Brand	Gianetti FAD



Allgemeine Produktabbildung. Artikel kann abweichen

## **Technical Informations**

Load capacity of rim 1 [kg]	1650
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	1485
Speed Rims 2 [km/h]	20
Maximum speed [km/h].	20
Nettogewicht [kg] (gültig)	18,80
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No