

## **RIMS**

Product group	Rims
Item number	32010178
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-5
Rim colour	Red
Brand	Accuride





## **Technical Informations**

Load capacity of rim 1 [kg]	2650
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	13,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Number of drain holes	2
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No