Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	32010179
Valid rim size	9.00 x 15.3
Rim connection	5/206/206
Offset (mm)	+34
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	1550
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	14,85
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	5
Bolt hole diameter [mm]	17
hub hole diameter [mm].	206
Bolt hole circle diameter [mm]	206
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No