

## RIMS

|                  |           |
|------------------|-----------|
| Product group    | Rims      |
| Item number      | 32010281  |
| Valid rim size   | 13 x 18   |
| Rim connection   | 8/221/275 |
| Bolt hole design | A3        |
| Rim colour       | Silver    |
| Brand            | Accuride  |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 4250                          |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 3350                          |
| Speed Rims 2 [km/h]         | 60                            |
| Maximum speed [km/h].       | 60                            |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 32,80                         |
| Hump                        | kein Hump                     |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |

---

|                                |                |
|--------------------------------|----------------|
| Cavity Sealed                  | No             |
| Verschweißung beidseitig       | No             |
| Ventilation holes              | No             |
| Rim centering                  | BC             |
| Number of bolt holes           | 8              |
| Bolt hole design EUWA          | B22 ES 36      |
| Bolt hole diameter [mm]        | 27             |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R18            |
| hub hole diameter [mm].        | 221            |
| Bolt hole circle diameter [mm] | 275            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |