

RIMS

| | |
|------------------|---------------------|
| Product group | Rims |
| Item number | 32012687 |
| Valid rim size | AG 20.00 x 22.5 TH2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A3 |
| Offset (mm) | -50 |
| Rim colour | Silver |
| Brand | Moveero |
| Rim series | Profiline |



Technical Informations

| | |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 7070 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 5310 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Towed axle |
| Nettogewicht [kg] (gültig) | 60,00 |
| Hump | TH2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |

| | |
|--------------------------------|------------------|
| Cavity Sealed | No |
| Disc thickness [mm] | 10 |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |