

## RIMS

Product group	Rims
Item number	32012688
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Brand	Moveero
Rim series	Profiline



## Technical Informations

Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	60,00
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

---

<b>Cavity Sealed</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	8
<b>Bolt hole design EUWA</b>	B22 ES 36
<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	221
<b>Bolt hole circle diameter [mm]</b>	275
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No