

RIMS

Product group	Rims
Item number	32012689
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Red
Brand	GKN
Rim series	Profiline





Technical Informations	
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5750
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	60,00
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No