

RIMS

Product group	Rims
Item number	32012880
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Brand	Moveero
Rim series	Profiline



Technical Informations

Load capacity of rim 1 [kg]	8840
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	85,00
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No