

RIMS

Product groupRimsItem number32012900Valid rim sizeAG 24.00 x 26.5 TH2Rim connection8/221/275Bolt hole designA2Rim colourSilverBrandGKNRim seriesProfiline		
Valid rim size AG 24.00 x 26.5 TH2 Rim connection 8/221/275 Bolt hole design A2 Rim colour Silver Brand GKN	Product group	Rims
Rim connection 8/221/275 Bolt hole design A2 Rim colour Silver Brand GKN	Item number	32012900
Bolt hole design A2 Rim colour Silver Brand GKN	Valid rim size	AG 24.00 x 26.5 TH2
Rim colour Silver Brand GKN	Rim connection	8/221/275
Brand GKN	Bolt hole design	A2
21	Rim colour	Silver
Rim series Profiline	Brand	GKN
	Rim series	Profiline





Technical Informations	
Load capacity of rim 1 [kg]	8570
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	85,00
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No