

RIMS

Product group	Rims
Item number	32013121
Valid rim size	AG 24.00 x 30.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Brand	Moveero
Rim series	Profiline



Technical Informations

Load capacity of rim 1 [kg]	11220
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	131,00
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No