

## RIMS

Product group	Rims
Item number	32013514
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Brand	Moveero



## Technical Informations

Load capacity of rim 1 [kg]	12240
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	153,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15

---

<b>Knurling</b>	without knurling
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	10
<b>Bolt hole design EUWA</b>	B22 DS 36
<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No