

RIMS

Product group	Rims
Item number	32013517
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Red
Brand	Moveero



Technical Informations

Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	14340
Speed Rims 3 [km/h]	15
Load capacity of rim 4 [kg]	11900
Speed of wheels 4 [km/h].	50
Maximum speed [km/h].	65
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	153,50

Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No