Bohnenkamp Moving Professionals

09.03.2025

RIMS

Product group	Rims
Item number	32013571
Valid rim size	36.00 - 32
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Brand	GKN





Technical Informations Load capacity of rim 1 [kg] 9250 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 40 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 269,50 Hump kein Hump Single / multi-part mehrteilig **Rim material** steel RAL RAL9006 **Cavity Sealed** No Verschweißung beidseitig No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No