

## **RIMS**

Product group	Rims
Item number	32013614
Valid rim size	11.25 - 25 / 2.0
Rim connection	20/459/511
Offset (mm)	+20
Rim colour	Black
Brand	Moveero



## **Technical Informations**

Load capacity of rim 1 [kg]	10000
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	30
Nettogewicht [kg] (gültig)	166,10
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	five-part
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Rim design industry	Standard

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Disc thickness [mm]	20
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	20
Bolt hole diameter [mm]	26
hub hole diameter [mm].	459
Bolt hole circle diameter [mm]	511
Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No